

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2017/0034500 A1 ARBABI et al.

Feb. 2, 2017 (43) **Pub. Date:**

(54) IMAGING APPARATUS AND IMAGE SENSOR INCLUDING THE SAME

(71) Applicants: SAMSUNG ELECTRONICS CO., LTD., Suwon-si (KR); CALIFORNIA INSTITUTE OF TECHNOLOGY,

Pasadena, CA (US)

(72) Inventors: Amir ARBABI, Pasadena, CA (US);

Seunghoon HAN, Suwon-si (KR); Andrei FARAON, Pasadena, CA (US)

(73) Assignees: SAMSUNG ELECTRONICS CO., LTD., Suwon-si (KR); CALIFORNIA

INSTITUTE OF TECHNOLOGY,

Pasadena, CA (US)

(21) Appl. No.: 15/221,719

(22) Filed: Jul. 28, 2016

Related U.S. Application Data

(60) Provisional application No. 62/198,268, filed on Jul. 29, 2015.

(30)Foreign Application Priority Data

Apr. 11, 2016 (KR) 10-2016-0044268

Publication Classification

(51) Int. Cl. H04N 13/02 (2006.01)G06T 7/00 (2006.01)H04N 13/00 (2006.01)

U.S. Cl.

CPC H04N 13/0228 (2013.01); H04N 13/0214 (2013.01); H04N 13/0037 (2013.01); H04N 13/004 (2013.01); G06T 7/0069 (2013.01); G06T 2207/10028 (2013.01)

ABSTRACT (57)

An image sensor includes a substrate, thin lenses disposed on a first surface of the substrate and configured to concentrate lights incident on the first surface, and light-sensing cells disposed on a second surface of the substrate, the second surface facing the first surface, and the light-sensing cells being configured to sense lights passing through the thin lenses, and generate electrical signals based on the sensed lights. A first thin lens and second thin lens of the thin lenses are configured to concentrate a first light and a second light, respectively, of the incident lights onto the lightsensing cells, the first light having a different wavelength than the second light.

